

C-SPAN Networks

C-SPAN C-SPAN2 C-SPAN3

Supported Receiver Models:

Digital Single-Channel Output

- **DSR4450** NTSC Analog Output
- **DSR4470** SDI Output
- **DSR6050** Transcoder
- **DSR6401** Transcoder

Digital Multiple Channel Output

- **DSR4410MD** Multi-Decrypter
- **DSR6300** Transcoder (3 CH)
- **DSR6402** Transcoder (2 CH)
- **DSR6403** Transcoder (3 CH)
- **DSR6404** Transcoder (4 CH)
- **DSR7401** Transcoder (12 CH SD)
- **DSR7403** Transcoder (3 CH)
- **DSR7406** Transcoder (6 CH)
- **DSR7412** Transcoder (12 CH)

Downlink Information



Satellite:

Galaxy 30 (125 Degrees West Longitude)

Polarity:

Vertical

Transponder:

C-Band Transponder 14 (3,980 MHz)

"Custom"/"LFreq" L-Band Tuning Frequency

1,170 MHz

Modulation Mode:

DVB-S2

Symbol Rate:

16.3

FEC:

8/9

VCT ID

932

C-SPAN

Channel **101** Standard Definition

Channel **201** High Definition

C-SPAN2

Channel **102** Standard Definition

Channel **202** High Definition

C-SPAN3

Channel **103** Standard Definition

Channel **203** High Definition