

# C-SPAN Networks

## C-SPAN<sup>®</sup> C-SPAN2 C-SPAN3<sup>®</sup>

### Supported Receiver Models:

Analog and Digital Single-Channel Output

- **DSR4410** with Firmware Version **1AE**
- **DSR4402X** with Firmware Version **15A**
- **DSR4550**

Digital Multi-Program Output

- **DSR4410MD** with Firmware Version **1B2**

High Definition

- **DSR6050** with Firmware Version **1C4**

DSR4410, 4402X, and 4550 have **Single** program output.

DSR4410MD has **Multiple** program output.

Motorola DSR4410 & DSR4402X IRDs provide both Analog and Digital (ASI) output of a single Standard Definition channel

DSR4410MD has only Digital output. (ASI & GIG)

MPEG-4 HD to MPEG-2 HD transcoding

### Downlink Information

Satellite:

**AMC 7 (Co-located with AMC 10)**

Polarity:

**Vertical**

Transponder:

**C-Band Transponder 19**

"Custom"/"LFreq" L-Band Tuning Frequency

**1070**

Modulation Mode:

**DCII Manual**

Symbol Rate:

**29.27 Msps**

FEC:

**3/4 Combined**

VCT ID

**932**



### **C-SPAN**

Channel **101** Standard Definition

Channel **201** High Definition

### **C-SPAN2**

Channel **102** Standard Definition

Channel **202** High Definition

### **C-SPAN3**

Channel **103** Standard Definition

Channel **203** High Definition